



# ThermoGlo™

Model NN4A

## Heated Display Cabinet

Item No: \_\_\_\_\_

AIA FILE NO. / SPEC NO.

CONSULTANT/ CONTRACTOR APPROVAL



The Marshall **Model NN4A** Heated Display Cabinet features our ThermoGlo™ heating technology. Heat radiates from every square inch of the upper flat plate surface. The need to clean intricate calrod, wire and reflector assemblies is eliminated. A precision microprocessor-type digital display and digital “set point” temperature controller maintain consistent product temperature.

The **NN4A** is comprised of two decks. Each deck has a separate power cord and can accommodate one full-size sheet pan. The unit’s rear hinged door reduces air-flow within the heated holding area and allows for easy product loading.

Marshall products are supported by a nationwide service organization and an in-house, full-time Customer Support Department. For parts, service or technical assistance, call:

**1-800-627-8368**

**ETL (US & Canada) & NSF Listed  
FOR COMMERCIAL USE ONLY**

*\*Ask about Marshall's companion High Speed Toasters,  
Conveyor Broilers and Ventilation Systems.*

**Marshall's Heated Display Cabinet incorporates ThermoGlo™ technology designed to solve demanding warming and holding requirements for a variety of food products.**

### FEATURES

- Microprocessor controls exact heat intensity to furnish a specific temperature.
- Delivers a wide range of temperature capabilities to fill exact warming and holding requirements.
- Flat surface allows for easy wipe-clean application.
- Food stays “presentation ready” longer because exact internal temperatures can be reached faster and maintained longer.

### CONSTRUCTION

- Heavy gauge stainless steel.
- Designed and built to custom specifications with heat radiating from the flat top surface.
- Designed with a flat unbreakable radiating metal face encased in stainless steel housing.
- Heavy gauge swing-down rear door with mirror type inner finish.
- Illumination provided by (4) 40 watt food grade coated bulbs for each deck.

### DIMENSIONS/SHIPPING

	<u>Exterior</u>	<u>Interior</u>
<b>Height:</b>	32.500"	12" each deck
<b>Width:</b>	28"	26"
<b>Depth:</b>	21"	20"
<b>Electrical:</b>	110/120V, 6 amps/deck (Domestic) 220/240V, 3 amps/deck (Int'l.)	
<b>Shipping Wt:</b>	150 lbs. (76 lbs per deck)	
<b>Option(s):</b>	Unit can be installed side-by-side or stacked as depicted. Height of non-stacked unit is 16.250 ". 4" legs available.	
<b>Power Cord:</b>	8' 3-wire ground type UL rated	

---

#### Marshall Air Systems, Inc.

419 Peachtree Drive South • Charlotte, North Carolina 28217 USA • Phone: (704) 525-6230 Fax: (704) 525-6229 • www.marshallair.com