



ThermoGlo™

Model Model TT1 Heated Display Cabinet

Item No: _____

AIA FILE NO. / SPEC NO.

CONSULTANT / CONTRACTOR APPROVAL



The Marshall **Model TT1** Heated Display Cabinet features our ThermoGlo™ technology. Heat radiates from every square inch of the upper flat plate heating surface. The need to clean intricate calrod, wire and reflector assemblies is eliminated. A precision microprocessor digital display and digital “set point” temperature controller maintain consistent product temperature. Food presentation is enhanced by mirror-type inner finish.

This illuminated cabinet accommodates any combination of sheet pans equal to 24" x 48". The unit's rear hinged door reduces air-flow within the heated holding area and allows for easy product loading.

All Marshall products are supported by a nationwide service organization and an in-house, full-time Customer Support Department. To place an order, call:

1-800-627-8368

**ETL (US & Canada) & NSF Listed
FOR COMMERCIAL USE ONLY**

**Ask about Marshall's companion High Speed Toasters, Conveyor Broilers and Ventilation Systems.*

Marshall's Heated Display Cabinet incorporates ThermoGlo™ technology designed to solve demanding warming and temperature requirements for fried chicken and other food products.

FEATURES

- Microprocessor controls exact heat intensity to furnish a specific temperature
- Delivers a wide range of temperature capabilities to fill exact warming and holding requirements
- Flat surface allows for easy wipe-clean application
- Food stays “presentation ready” longer because exact internal temperatures can be reached faster and maintained longer

CONSTRUCTION

- Heavy gauge stainless steel
- Designed and built to custom specifications with heat radiating from the flat top surface
- Designed with a flat unbreakable radiating metal face encased in stainless steel housing
- Heavy gauge swing-down rear door with mirror type inner finish
- Illumination is provided by (4) 40-watt food grade coated bulbs.

DIMENSIONS/SHIPPING

Height:	16.250"
Width:	28"
Depth:	23.750"
Electrical:	110/120V, AC 840W, 60Hz, 7 amps
Shipping Wt:	83 lbs.
Option:	Can be stacked. 4" legs.
Power Cord:	6 ft 3-wire grounding type UL rated

Marshall Air Systems, Inc.

419 Peachtree Drive South • Charlotte, North Carolina 28217 USA • Phone: (704) 525-6230 Fax: (704) 525-6229 • www.marshallair.com